

**Microprocessor Engineering Limited**

c Published by Microprocessor  
Engineering Copyright © 2003, 2005,  
2007, 2009, 2013 Microprocessor  
Engineering Limited  
MSP430 Lite Target v7.3  
User manual Manual,  
revision 7.3 22 June 2014  
Software Software version 7.3

For technical support Please contact  
your supplier

For further information  
MicroProcessor Engineering Limited  
133 Hill Lane Southampton SO15 5AF UK  
Tel +44 (0)23 8063 1441  
Fax +44 (0)23 8033 9691  
e-mail mpe@mpeforth.com  
e-mail tech-support@mpeforth.com  
web www.mpeforth.com

How to read the Glossary

Forth words are printed in upper case 1- \ n -- n-1  
followed by a picture of the data 2- \ n -- n-2  
stack, seperated by a backslash, the 2\* \ n1 -- n2  
forth comment sign. This is done in U2/ \ n1 -- n2  
the corosscompiler source to 2/ \ n1 -- n2  
seperate the definition from a - \ n1 n2 -- n1-n2  
comment on it. Since the glossary is + \ n1 n2 -- n1+n2  
mostly generated automatic, this NEGATE \ n1 ---n1  
commenting stype is kept in this ABS \ n1 --|n1|  
printing. There may be complex stack DNEGATE \ d1 ---d1  
pictures. Only those forth words are DABS \ d1 --|d1|  
given here, that are output by WORDS D+ \ d1 d2 -- d3  
to Terminal.

-----  
**4.2 Literal and flow of control**

EXECUTE \ xt --  
I \ --n  
J \ --n  
UNLOOP \ --  
LEAVE \ --

**4.3 Flash operations**

FERASE \ addr len --

C!F \ b addr --  
!F \ w addr --

**4.4 Digits and strings**

DIGIT \ char base -- 0 | n true  
/SRTING \ addr len n -- addr+n len-n  
CMOVE \ source dest len --  
CMOVE> \ source dest len --  
FILL \ addr len char --  
ERASE \ addr len --  
S= \ addrl addr2 count --flag  
SKIP \ c-addr u char -- 'c-addr 'u  
SCAN \ caddr u char -- caddr2 u2  
(") \ --addr  
UPC \ char -- char  
UPPER \ c-addr len --  
PLACE \ c-addr1 u c-addr2 --

**4.5 Arithmetic**

**4.5.1 Basics**

1+ \ n -- n+1  
2+ \ n -- n+2

2- \ n -- n-2  
2\* \ n1 -- n2  
U2/ \ n1 -- n2  
2/ \ n1 -- n2  
- \ n1 n2 -- n1-n2  
+ \ n1 n2 -- n1+n2  
NEGATE \ n1 ---n1  
ABS \ n1 --|n1|  
DNEGATE \ d1 ---d1  
DABS \ d1 --|d1|  
D+ \ d1 d2 -- d3  
D- \ d1 d2 -- d1-d2  
S>D \ n -- d  
D< \ d1 d2 -- t/f  
D> \ d1 d2-- t/f  
D0= \ d -- t/f  
D= \ d1 d2 -- t/f

**4.5.2 Multiplication**  
UM\* \ u1 u2 -- ud  
\* \ n1 n2 -- n1\*n2

M\* \ n1 n2 -- d

**4.5.3 Division**  
UM/MOD \ u32 u16 --urem uquot  
SM/REM \ d n --rem quot  
/MOD \ n1 n2 --rem quot  
/ \ n1 n2 -- quot  
MOD \ n1 n2 -- rem  
MU/MOD \ ud1 u2 --u3 ud4

**4.6 Logic**

AND \ n1 n2 -- n3  
OR \ n1 n2 -- n3  
XOR \ n1 n2 -- n3  
INVERT \ n1 --n2

**4.7 Shifts**

LSHIFT \ x count --x<sup>0</sup>  
RSHIFT \ x count --x<sup>0</sup>

**4.8 Return stack words**

>R \ x -- ; R -- x  
R@ \ --x ; R x -- x  
R> \ --x ; R:x--

**4.9 Comparisons**

= \ n1 n2 -- flag  
<> \ n1 n2 -- flag  
0<> \ n -- flag  
0= \ n -- flag  
0< \ n -- flag  
0> \ n -- flag  
U< \ n1 n2 -- flag  
U> \ n1 n2 -- flag

< \ n1 n2 -- t/f  
> \ n1 n2 -- t/f  
<= \ n1 n2 -- t/f  
>= \ n1 n2 -- t/f

MIN \ n1 n2 -- min(n1,n2)  
MAX \ n1 n2 -- max(n1,n2)

**4.10 Stack primitives**

OVER \ n1 n2 -- n1 n2 n1  
2OVER \ n1 n2 n3 n4 -- n1 n2 n3 n4 n1  
n2  
DROP \ n1 --

2DROP \ n1 n2 --  
SWAP \ n1 n2 - n2 n1  
2SWAP \ n1 n2 n3 n4 -- n3 n4 n1 n2  
DUP \ n1 -- n1 n1  
2DUP \ n1 n2 -- n1 n2 n1 n2  
?DUP \ n1 -- n1 [n1]  
NIP \ n1 n2 -- n2  
TUCK \ n1 n2 -- n2 n1 n2  
PICK \ nn..n0 n -- nn..n0 nn  
ROT \ n1 n2 n3 -- n2 n3 n1  
-ROT \ n1 n2 n3 -- n3 n1 n2  
C@ \ addr -- b  
@ \ addr -- n  
2@ \ addr -- d  
C! \ b addr --  
! \ n addr --  
2! \ d addr --  
+! \ n addr --  
NOOP \ -- ; dummy  
WITHIN \ n1|u1 n2|u2 n3|u3 -- flag  
ON \ addr --  
OFF \ addr --  
BOUNDS \ addr len -- addr+len addr  
NAME> \ nfa -- cfa  
>NAME \ cfa -- nfa  
SEARCH-WORDLIST \ c-addr u wid --0|xt  
1|xt -1

**4.11 Portability words**

CELL \ -- 2  
ALIGNED \ addr --addr  
>BODY \ xt -- pfa  
COMPILE, \ addr --

**4.12 Defining words**

DOES> \ C: colon-sys1 -- colon-sys2 ;  
Run: -- ; R nest-sys --  
  \ C: "<spaces>name" -- colon-sys ;  
Exec i\*x --j\*x ; R -- nest-sys  
CONSTANT \ x "<spaces>name" -- ; Exec  
--x  
EQU \ x "<spaces>name" -- ; Exec --x  
VARIABLE \ "<spaces>name" -- ; Exec  
--a-addr  
USER \ u "<spaces>name" -- ; Exec  
--addr  
DEFER \ Comp "<spaces>name" -- ; Run:  
i\*x --j\*x

' <action> IS <deferredword>  
['] <action> IS <deferredword>

#### 4.13 Multitasker hook

PAUSE \ --

#### 4.14 Reboot

REBOOT \ --

#### 5.1 User variables

SELF \ addr  
S0 \ -- addr  
R0 \ -- addr  
'TIB \ -- addr  
#TIB \ -- n  
>IN \ -- n  
OUT \ -- n  
DPL \ -- addr  
OPVEC \ -- addr  
IPVEC \ -- addr  
PAD \ -- addr

#### 5.2 System data

##### 5.2.1 Constants

BL \ -- char

##### 5.2.2 System variables and data

FENCE \ -- addr  
DP \ -- addr  
RP \ -- addr  
XDP \ --addr  
DISK-ERROR \ -- addr

#### 5.3 Vectored I/O handling

(see user manual)

#### 5.3.3 Generic I/O words

KEY \ --char  
KEY? \ --flag  
EMIT \ --char  
CR \ --  
SPACE \ --  
SPACES \ n --

#### 5.4 Laying data in memory

HERE \ -- addr  
ORG \ addr --  
ALLOT \ n --

RHERE \ -- addr

RALLOT \ n --

ROM \ --

RAM \ --

ALIGNED \ addr --addr'

ALIGN \ --

, \ x --

C, \ char --

#### 5.5 Dictionary management

FIND \ c-addr -- c-addr 0|xt 1|xt -1  
.NAME \ nfa --  
CREATE \ --  
<BUILDS \ --

#### 5.6 String compilation

5.7 ANS words CATCH and THROW  
(see user manual)

#### 5.7.3 User words

CATCH \ i\*x xt -- j\*x 0|i\*x n  
THROW \ k\*x n -- k\*x|i\*x n  
?THROW \ flag throw- -- ;  
ABORT" \ Comp "ccc" -- ; Run:  
i\*x xl --| i\*x ; R j\*x --| j\*x

#### 5.8 Formatted and unformatted i/o

5.8.1 Setting number bases  
HEX \ --  
DECIMAL \ --

#### 5.8.2 Numeric output

HOLD \ char --  
# \ ud1 -- ud2  
#S \ ud1 -- ud2  
<\ --  
#> \ xd -- c-addr u  
D.R \ dn --  
D. \ d --  
. \ n --  
U. \ u --  
.R \ n1 n2 --

#### 5.8.3 Numeric input

+DIGIT \ d1 n --d2  
>NUMBER \ ud1 c-addr1 u1 --ud2 c-addr2 u2  
NUMBER? \ \$addr -- n1|d2|0

#### 5.9 String input and output

. " \ "ccc" --  
\$. \ c-addr --  
ACCEPT \ c-addr +n1 --+n2  
TYPE \ c-addr len --

#### 5.10 Source input control

QUERY \ --

#### 5.11 Text scanning

PARSE \ char "ccc<char>" --c-addr u  
WORD \ char "<chars>ccc<char>" --c-addr

#### 5.12 Miscellaneous

WORDS \ --  
MOVE \ addr1 addr2 u --  
DEPTH \ ??? -- +n  
TESTAPP \ -- ; endless loop, reset to leave loop.

#### 5.13 Wordlist control

(see user manual)

#### 5.14 Control structures

DO \ C: -- do-sys ; Run: n1|u1 n2|u2 -- ; R -- loop-sys  
?DO \ C: -- do-sys ; Run: n1|u1 n2|u2 -- ; R -- | loop-sys  
LOOP \ C: do-sys -- ; Run: -- ; R loop-sys1 -- | loop-sys2  
+LOOP \ C: do-sys -- ; Run: n -- ; R loop-sys1 -- | loop-sys2  
BEGIN \ C: -- dest ; Run: --  
AGAIN \ C: dest -- ; Run: --  
UNTIL \ C: dest - ; Run: x --  
WHILE \ C: dest -- orig dest ; Run: x --  
--  
REPEAT \ C: orig dest -- ; Run: --  
IF \ C: -- orig ; Run: x--  
THEN \ C: orig -- ; Run: --  
ELSE \ C: orig1 -- orig2 ; Run: --  
RECURSE \ Comp --

#### 5.15 Target interpreter and compiler

POSTPONE \ Comp "<spaces>name" --

S" \ Comp "ccc" -- ; Run: --c-addr u  
C" \ Comp "ccc" -- ; Run: --c-addr

LITERAL \ Comp x -- ; Run: -- x

[CHAR] \ Comp "<spaces>name" -- ; Run: -- char

[ \ --

] \ --

IMMEDIATE \ --

' \ "<spaces>name" --xt

['] \ Comp "<spaces>name" -- ; Run: --xt

[COMPILE] \ "<spaces>name" --

( \ "ccc<paren>" --

\ \ "ccc<eol>" --

", \ "ccc<quote>" --

IS \ "<spaces>name" --

EXIT \ R nest-sys --

; \ C: colon-sys -- ; Run: -- ; R nest-sys --

INTERPRET \ --

EVALUATE \ i\*x c-addr u -- j\*x

QUIT \ -- ; R i\*x --

#### 5.16 Startup

##### 5.16.1 The COLD sequence

COMMIT \ xt|0 --

EMPTY \ --

COLD \ --

#### 6. Time Delays

TICKS \ -- n

LATER \ n --n'

TIMEDOUT? \ n -- flag

MS \ n --

#### 7. Debug tools

DUMP \ addr len --

.S \ i\*x -- i\*x

#### 8. Compile source from AIDE

END-LOAD \ --

INCLUDE \ "<filename>" --

#### 11.2 UART

CONSOLE0 \ -- addr

CONSOLE \ -- addr

TYPE \ c-addr len --

#### 12. Ticker using watchdog timer

```
<TICKS> \ -- addr ; variable
TICKS \ -- n
LEDACTIVE \ -- addr
START-CLOCK \ --
STOP-CLOCK \ --
```

#### 13.1 Basic port usage

(see user manual)

```
GREEN-ON \ -- ; P1.6
GREEN-OFF \ -- ; P1.6
RED-ON \ -- ; P1.0
RED-OFF \ -- ; P1.0
```

#### 13.2 Port counting using interrupts

#### 13.3 Simple ADC driver

(see user manual)

#### 5.17 Kernel error codes

```
-1 ABORT
-2 ABORT"
-4 Stack underflow
-13 Undefined word.
-14 Attempt to interpret a compile
only definition.
-22 Control structure mismatch
-unbalanced control structure.
-121 Attempt to remove with MARKER
or FORGET below FENCE in protected
dictionary.
-403 Attempt to compile an interpret
only definition.
-501 Error if not LOADING block.
```

#### 3. MSP430G2553 start up

##### 3.1 Magic addresses

\$10FF	CALBC1_1MHz
\$10FE	CALDCO_1MHz
\$10FD	CALBC1_8MHz
\$10FC	CALDCO_8MHz
\$10FB	CALBC1_12MHz
\$10FA	CALDCO_12MHz
\$10F9	CALBC1_16MHz
\$10F8	CALDCO_16MHz
\$10F7 08	Size (bytes) of value data
\$10F6 01	Tag

#### Memory Map

.. peripherals
\$0200 - \$0400 RAM
\$1000 - \$10FF INFO 4 segments of 64 bytes flash
.. nc
\$C000 - \$CFFF application flash (4K)
\$D000 - \$FFFF liteLP2553sa code (12287 bytes)

#### RAM downwards

\$0400 ( R0 @ )
... returnstack, &64 (\$40) bytes down
\$03BC ( S0 @ )
... datastack, &64 (\$40) bytes down
\$032C ( PAD )
... scrach pad
\$02E0
... terminal input buffer, &64 (\$40) bytes up
\$02A0 ( 'TIB @ )
... unused RAM, &40 cells up, variables
\$024E ( RHERE )
... system user variables
\$0200

#### 4. MSP430 definitions

4.1 Register usage
IP R0/PC
RSP R1/SP
R2/CG1/SR
R3/CG2
PSP R4
TOS R5
UP R6
LP (locals) R7
scratch R8..R13
codegen R14 temp
codegen R15 SR

INFO segments
\$1000 info-D
\$1040 info-C APPSTART forth system information.
\$1080 info-B
\$10C0 info-A Segment A contains calibration data.

(M.Kalus, 10/2014)

MSP430 Lite Target Glossary - User WORDS of stand alone version - MCU is MSP430G2553

Alphanumeric List	loop-sys1 --   loop-sys2 < \ n1 n2 -- t/f <# \ -- <= \ n1 n2 -- t/f <> \ n1 n2 -- flag <BUILDS \ -- <TICKS> \ -- adr = \ n1 n2 -- flag > \ n1 n2 -- t/f >= \ n1 n2 -- t/f >BODY \ xt -- pfa >IN \ -- n >NAME \ cfa -- nfa >NUMBER \ udl c-addr1 u1 --ud2 c- addr2 u2 >R \ x -- ; R -- x \$. \ c-addr -- 0< \ n -- flag 0<> \ n -- flag 0= \ n -- flag 0> \ n -- flag 1- \ n -- n-1 1+ \ n -- n+1 2- \ n -- n-2 2! \ d addr -- 2@ \ addr -- d 2* \ n1 -- n2 2/ \ n1 -- n2 2+ \ n -- n+2 2DROP \ n1 n2 -- 2DUP \ n1 n2 -- n1 n2 n1 n2 2OVER \ n1 n2 n3 n4 -- n1 n2 n3 n4 n1 n2 2SWAP \ n1 n2 n3 n4 -- n3 n4 n1 n2 ABORT" \ Comp "ccc <quote>" -- ; Run:            i*x x1 --  i*x ; R j*x --  j*x            ABS \ n1 -- n1             ACCEPT \ c-addr +n1 --+n2            AGAIN \ C: dest -- ; Run: --            ALIGN \ --            ALIGNED \ addr --addr            ALIGNED \ addr --addr'            ALLOT \ n --            AND \ n1 n2 -- n3            BEGIN \ C: -- dest ; Run: --            BL \ -- char            BOUNDS \ addr len -- addr+len addr            C, \ char --         </quote>	C! \ b addr -- C!F \ b addr -- C" \ Comp "ccc <quote>" -- ; Run: --            c-addr            C@ \ addr -- b            CATCH \ i*x xt -- j*x 0 i*x n            CELL \ -- 2            CMOVE \ source dest len --            CMOVE&gt; \ source dest len --            COLD \ --            COMMIT \ xt 0 --            COMPILE, \ addr --            CONSOLE \ -- addr            CONSOLE0 \ -- addr            CONSTANT \ x "&lt;spaces&gt;name" -- ; Exec            --x            COUNT \ addr --addr+1 len            CR \ --            CREATE \ --            D- \ d1 d2 -- d1-d2            D. \ d --            D.R \ dn --            D+ \ d1 d2 -- d3            D&lt; \ d1 d2 -- t/f            D= \ d1 d2 -- t/f            D&gt; \ d1 d2-- t/f            D0= \ d -- t/f            DABS \ d1 -- d1             DECIMAL \ --            DEFER \ Comp "&lt;spaces&gt;name" -- ; Run:            i*x --j*x            DEPTH \ ??? -- +n            DIGIT \ char base -- 0   n true            DISK-ERROR \ -- addr ; variable            DNEGATE \ d1 ---d1            DO \ C: -- do-sys ; Run: n1 u1 n2 u2            -- ; R -- loop-sys            DOES&gt; \ C: colon-sys1 -- colon-sys2 ;            Run: -- ; R nest-sys --            DP \ -- addr            DPL \ -- addr            DROP \ n1 --            DUMP \ addr len --            DUP \ n1 -- n1 n1            ELSE \ C: orig1 -- orig2 ; Run: --            EMIT \ --char            EMPTY \ --            END-LOAD \ --         </quote>	EQU \ x "<spaces>name" -- ; Exec --x ERASE \ addr len -- EVALUATE \ i*x c-addr u -- j*x EXECUTE \ xt -- EXIT \ R nest-sys -- FENCE \ -- addr FILL \ addr len char -- FIND \ c-addr -- c-addr 0 xt 1 xt -1 FLERASE \ addr len -- GREEN-OFF \ -- ; P1.6 GREEN-ON \ -- ; P1.6 HERE \ --addr HEX \ -- HOLD \ char -- I \ -- IF \ C: -- orig ; Run: x-- IMMEDIATE \ -- INCLUDE \ "<filename>" -- INTERPRET \ -- INVERT \ n1 --n2 IPVEC \ -- addr IS \ "<spaces>name" -- J \ --n KEY \ --char KEY? \ --flag LATER \ n --n' LEAVE \ -- LEDACTIVE \ -- addr LITERAL \ Comp x -- ; Run: -- x LOOP \ C: do-sys -- ; Run: -- ; R loop-sys1 --   loop-sys2 LSHIFT \ x count --x M* \ n1 n2 -- d MAX \ n1 n2 -- max(n1,n2) MIN \ n1 n2 -- min(n1,n2) MOD \ n1 n2 -- rem MOVE \ addr1 addr2 u -- MS \ n -- MU/MOD \ udl u2 --u3 ud4 NAME> \ nfa -- cfa NEGATE \ n1 ---n1 NIP \ n1 n2 -- n2 NOOP \ -- ; dummy NUMBER? \ \$addr -- n1 d2 0 OFF \ addr -- ON \ addr -- OPVEC \ -- addr OR \ n1 n2 -- n3
-------------------	--	--	---

**MSP430 Lite Target Glossary - User WORDS of stand alone version - MCU is MSP430G2553**

```
ORG \ addr --
OUT \ -- n
OVER \ n1 n2 -- n1 n2 n1
PAD \ -- addr
PARSE \ char "ccc<char>" --c-addr u
PAUSE \ --
PICK \ nn..n0 n -- nn..n0 nn
PLACE \ c-addr1 u c-addr2 --
POSTPONE \ Comp "<spaces>name" --
QUERY \ --
QUIT \ -- ; R i*x --
R@ \ --x ; R x -- x
R> \ --x ; R:x--
R0 \ -- addr
RALLOT \ n --
RAM \ --
REBOOT \ --
RECURSE \ Comp --
RED-OFF \ -- ; P1.0
RED-ON \ -- ; P1.0
REPEAT \ C: orig dest -- ; Run: --
RHERE \ --addr
ROM \ --
ROT \ n1 n2 n3 -- n2 n3 n1
RP \ -- addr
RSHIFT \ x count --xÓ
S" \ Comp "ccc<quote>" -- ; Run: --
c-addr u
S= \ addr1 addr2 count --flag
S>D \ n -- d
S0 \ -- addr
SCAN \ caddr u char -- caddr2 u2
SEARCH-WORDLIST \ c-addr u wid --0|xt
1|xt -1
SELF \ task identifier and TCB
SKIP \ c-addr u char -- 'c-addr 'u
SM/REM \ d n --rem quot
SPACE \ --
SPACES \ n --
START-CLOCK \ --
STOP-CLOCK \ --
SWAP \ n1 n2 - n2 n1
TESTAPP \ -- ; endless loop, reset to
leave loop.
THEN \ C: orig -- ; Run: --
THROW \ k*x n -- k*x|i*x n
TICKS \ -- n
TICKS \ -- n
```