

# **Working Draft Project American National Standard**

**T10/2095-D**

**Revision 1  
July 9, 2008**

---

## **Information technology - USB Attached SCSI (UAS)**

This is an internal working document of T10, a Technical Committee of Accredited Standards Committee INCITS (International Committee for Information Technology Standards). As such this is not a completed standard and has not been approved. The contents may be modified by the T10 Technical Committee. The contents are actively being modified by T10. This document is made available for review and comment only.

Permission is granted to members of INCITS, its technical committees, and their associated task groups to reproduce this document for the purposes of INCITS standardization activities without further permission, provided this notice is included. All other rights are reserved. Any duplication of this document for commercial or for-profit use is strictly prohibited.

T13 Technical Editor:

Curtis E. Stevens  
Western Digital Technologies, Inc.  
20511 Lake Forest Dr.  
Lake Forest, Ca. 92630  
USA

Telephone: 949-672-7933  
Email: Curtis.Stevens@wdc.com

---

Reference number  
ISO/IEC xxxx-xxx:200x  
ANSI INCITS \*\*\*-200x

## Points of Contact

### International Committee for Information Technology Standards (INCITS) T10 Technical Committee

#### T10 Chair

John B. Lohmeyer  
LSI Corporation  
4420 ArrowsWest Drive  
Colorado Springs, CO 80907-3444  
USA

Telephone: (719) 533-7560  
Email: lohmeier@t10.org

T10 Web Site: <http://www.t10.org>

T10 E-mail reflector:

Server: majordomo@t10.org

To subscribe send e-mail with 'subscribe' in message body

To unsubscribe send e-mail with 'unsubscribe' in message body

#### T10 Vice-Chair

Mark S. Evans  
Western Digital Corporation  
5836 Rue Ferrari  
San Jose, CA 95138  
USA

Telephone: (408) 363-5257  
Email: mark.evans@wdc.com

#### INCITS Secretariat

Suite 200  
1250 Eye Street, NW  
Washington, DC 20005  
USA

Telephone: 202-737-8888  
Web site: <http://www.incits.org>  
Email: incits@itic.org

#### Information Technology Industry Council

Web site: <http://www.itic.org>

#### Document Distribution

INCITS Online Store  
managed by Techstreet  
1327 Jones Drive  
Ann Arbor, MI 48105  
USA

Web site: <http://www.techstreet.com/incits.html>  
Telephone: (734) 302-7801 or (800) 699-9277

Global Engineering Documents, an IHS Company  
15 Inverness Way East  
Englewood, CO 80112-5704  
USA

Web site: <http://global.ihs.com>  
Telephone: (303) 397-7956 or (303) 792-2181 or (800) 854-7179

American National Standard  
for Information Technology

## **USB Attached SCSI**

Secretariat  
Information Technology Industry Council

Approved mm.dd.yy

American National Standards Institute, Inc.

### **ABSTRACT**

This standard specifies the requirements for the USB Attached SCSI (UAS) transport protocol. The UAS transport protocol defines a mechanism to transport SCSI commands using USB hardware. The UAS transport protocol coordinates with other members of the SCSI family of standards via the SAM-4 architecture model. This standard is intended to be used in conjunction with SCSI command set standards and USB specifications.

## American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that effort be made towards their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give interpretation on any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

**CAUTION NOTICE:** This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

[The patent statement goes here.](#)

[If no patents have been disclosed place the statement in 5.5.2 shall be used.](#)

[If any patents have been disclosed place the statement in 5.5.3 shall be used.](#)

Published by

**American National Standards Institute  
11 W. 42nd Street, New York, New York 10036**

Copyright © 2008 by Information Technology Industry Council (ITI). All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of ITI, 1250 Eye Street NW, Suite 200, Washington, DC 20005.

Printed in the United States of America

## Document Status

Document 08-xxxx is the issues list for this draft. 08-xxxx contains a list of the issues associated with the document, an issue number that remains assigned to the issue for the life of document development, a resolution to the issue, an owner for the issue, and a disposition for the issue.

Revision History		
Rev	Date	Description
0	January 29, 2008	1) Initial revision

## New Capabilities added to UAS

Integrated Proposal List		
#	Doc	Description
1		No proposals integrated.
2		
3		
4		



## Contents

	Page
Points of Contact.....	ii
Document Status .....	v
New Capabilities added to UAS .....	v
Contents.....	vii
Tables .....	ix
Figures .....	xi
Foreword .....	xiii
Introduction .....	xiii
1 Scope .....	1
2 Normative references .....	2
2.1 Normative References .....	2
2.2 Approved references .....	2
2.3 References under development .....	3
2.4 Other references .....	3
3 Definitions, symbols, abbreviations, and conventions .....	4
3.1 Definitions .....	4
3.2 Symbols and abbreviations .....	4
3.3 Keywords .....	5
3.4 Editorial conventions .....	5
3.5 Numeric and character conventions .....	6
3.5.1 Numeric conventions .....	6
3.5.2 Byte encoded character strings conventions .....	6
4 Model .....	8
4.1 Overview .....	8
4.2 Placeholder .....	8
5 USB .....	9
5.1 Overview .....	9
5.2 Backward Compatibility .....	9
5.3 USB Resource Requirements .....	9
5.3.1 Overview .....	9
5.3.2 USB Class Specific Requests .....	9
5.3.3 USB Descriptors .....	9
5.4 Backward Compatibility .....	11
6 Transport .....	12
6.1 Overview .....	12
6.2 Information Units .....	12
6.2.1 Overview .....	12
6.2.2 Command IU .....	12
6.2.3 Read Ready IU .....	13
6.2.4 Write Ready IU .....	13
6.2.5 Status IUs .....	14

6.2.6 Task Management IU .....	15
6.3 Information Unit Sequences .....	17
6.3.1 Send Data-In .....	17
6.3.2 Receive Data-Out .....	17
6.4 Transport Requirements .....	17
6.4.1 Data Transfer Transport Portocol Services .....	17
6.5 Asynchronous Notification .....	17
6.6 Virtualization .....	17
Annex A (Normative) Place Holder .....	19
A.1 Overview .....	19



## Tables

	Page
Table 1 - Standards bodies .....	2
Table 2 - Numbering conventions .....	6
Table 3 - USB Device Descriptor .....	9
Table 4 - USB Configuration Descriptor .....	10
Table 5 - USB Interface Descriptor .....	10
Table 6 - USB Bulk-In Endpoint Descriptor .....	11
Table 7 - USB Bulk-Out Endpoint Descriptor .....	11
Table 8 - IU Identifier Summary .....	12
Table 9 - Command IU .....	12
Table 10 - task attribute field .....	13
Table 11 - Read Ready IU .....	13
Table 12 - Write Ready IU .....	13
Table 13 - Sense IU .....	14
Table 14 - Response IU .....	14
Table 15 - response code field .....	15
Table 16 - Task Management IU .....	15
Table 17 - Task Management Functions .....	16



## Figures

	Page
Figure 1 - SCSI document relationships .....	1



## Foreword

This foreword is not part of American National Standard INCITS \*\*\*-200x.

The purpose of this standard is to define requirements for a USB protocol that is SAM-4 compliant.

With any technical document there may arise questions of interpretation as new products are implemented. INCITS has established procedures to issue technical opinions concerning the standards developed by INCITS. These procedures may result in SCSI Technical Information Bulletins being published by INCITS.

These Bulletins, while reflecting the opinion of the Technical Committee that developed the standard, are intended solely as supplementary information to other users of the standard. This standard, ANSI INCITS \*\*\*-200x, as approved through the publication and voting procedures of the American National Standards Institute, is not altered by these bulletins. Any subsequent revision to this standard may or may not reflect the contents of these Technical Information Bulletins.

Current INCITS practice is to make Technical Information Bulletins available through:

INCITS Online Store	<a href="http://www.techstreet.com/INCITS.html">http://www.techstreet.com/INCITS.html</a>
managed by Techstreet	Telephone: 1-734-302-7801 or
1327 Jones Drive	1-800-699-9277
Ann Arbor, MI 48105	Facsimile: 1-734-302-7811

or

Global Engineering	<a href="http://global.ihs.com/">http://global.ihs.com/</a>
15 Inverness Way East	Telephone: 1-303-792-2181 or
Englewood, CO 80112-5704	1-800-854-7179
	Facsimile: 1-303-792-2192

Requests for interpretation, suggestions for improvement and addenda, or defect reports are welcome. They should be sent to the INCITS Secretariat, National Committee for Information Technology Standards, Information Technology Institute, 1250 Eye Street, NW, Suite 200, Washington, DC 20005- 3922.

This standard was processed and approved for submittal to ANSI by the InterNational Committee for Information Technology Standards (INCITS). Committee approval of the standard does not necessarily imply that all committee members voted for approval. At the time of it approved this standard, INCITS had the following members:

<<Insert INCITS member list>>

The INCITS Technical Committee T10 on SCSI Storage Interfaces, that reviewed this standard, had the following members:

## Introduction

This standard encompasses the following:

Clause 1 describes the scope.

Clause 2 provides normative references for the entire standard.

Clause 3 provides definitions, abbreviations, and conventions used within the entire standard.

Clause 4 describes Models.

Clause 5 describes USB requirements.

Clause 6 describes Transport requirements.

Annex A is a placeholder




# USB Attached SCSI (UAS)

## 1 Scope

The SCSI family of standards provides for many different transport protocols that define the rules for exchanging information between different SCSI devices. This standard defines the rules for exchanging information between SCSI devices using a USB interconnect. Other SCSI transport protocol standards define the rules for exchanging information between SCSI devices using other interconnects.

Figure 1 shows the relationship of this standard to the other standards and related projects in the SCSI family of standards.



**Figure 1 — SCSI document relationships**

USB Attached SCSI is a new generation of USB Transport Standards. This standard supports the following features in support of USB-2 and future USB specifications:

- a) does not interfere with the USB Mass Storage Class (MSC) bulk-only transport;
- b) mechanism to send commands associated with any T10 standard to a USB device;
- c) support for queuing in the protocol;
- d) support for autosense;
- e) compliance with SCSI Architecture Model - 4 (SAM-4) or later; and
- f) other capabilities.

## 2 Normative references

### 2.1 Normative References

Referenced standards and specifications contain provisions that, by reference in the text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed below.

Copies of the following documents may be obtained from ANSI:

- a) approved ANSI standards;
- b) approved and draft international and regional standards (e.g., ISO, IEC); and
- c) approved and draft foreign standards (e.g., JIS and DIN).

For further information, contact ANSI Customer Service Department at 212-642-4900 (phone), 212-302-1286 (fax) or via the World Wide Web at <http://www.ansi.org>.

Additional availability contact information is provided below as needed.

Table 1 shows standards bodies and their web sites.

**Table 1 — Standards bodies**

Abbreviation	Standards body	Web site
ANSI	American National Standards Institute	<a href="http://www.ansi.org">http://www.ansi.org</a>
DIN	German Institute for Standardization	<a href="http://www.din.de">http://www.din.de</a>
IEC	International Engineering Consortium	<a href="http://www.iec.ch">http://www.iec.ch</a>
IEEE	Institute of Electrical and Electronics Engineers	<a href="http://www.ieee.org">http://www.ieee.org</a>
INCITS	International Committee for Information Technology Standards	<a href="http://www.incits.org">http://www.incits.org</a>
ISO	International Standards Organization	<a href="http://www.iso.ch">http://www.iso.ch</a>
ITI	Information Technology Industry Council	<a href="http://www.itic.org">http://www.itic.org</a>
JIS	Japanese Industrial Standards Committee	<a href="http://www.jisc.org">http://www.jisc.org</a>
T10	INCITS T10 SCSI storage interfaces	<a href="http://www.t10.org">http://www.t10.org</a>
T11	INCITS T11 Fibre Channel interfaces	<a href="http://www.t11.org">http://www.t11.org</a>
T13	INCITS T13 ATA storage interface	<a href="http://www.t13.org">http://www.t13.org</a>

Additional availability contact information is provided below as needed.

### 2.2 Approved references

At the time of publication, the following referenced standards or technical reports were approved:

---



---

[Editor's Note 1: This approved reference is just a placeholder for formatting.](#)

---



---

ANSI INCITS TR-35-2004, *Methodologies for Jitter and Signal Quality Specification (MJSQ)*. When MJSQ is referenced from this standard, the FC Port terminology used within MJSQ should be substituted with SAS phy terminology.



## 2.3 References under development

At the time of publication, the following referenced standards were still under development. For information on the current status of the document, or regarding availability, contact the relevant standards body or other organization as indicated.

ISO/IEC 14776-414, *SCSI Architecture Model-4 (SAM-4)* (T10/1683-D)

ISO/IEC 14776-454, *SCSI Primary Commands-4 (SPC-4)* (T10/1731-D)

ISO/IEC 14776-323, *SCSI Block Commands-3 (SBC-3)* (T10/1799-D)

ISO/IEC 14776-372, *SCSI Enclosure Services-2 (SES-2)* (T10/1559-D)

NOTE 1 — For more information on the current status of these documents, contact the INCITS Secretariat at 202-737-8888 (phone), 202-638-4922 (fax) or via Email at [incits@itic.org](mailto:incits@itic.org). To obtain copies of these documents, contact Global Engineering at 15 Inverness Way, East Englewood, CO 80112-5704 at 303-792-2181 (phone), 800-854-7179 (phone), or 303-792-2192 (fax) or see <http://www.incits.org>.

## 2.4 Other references

For information on the current status of the listed documents, or regarding availability, contact the indicated organization.

*Universal Serial Bus Specification Rev 2.0 (USB-20)*. April 27, 2000

*Universal Serial Bus Mass Storage Class Specification Overview Rev 1.2 (MSC-12)*. June 23, 2003

NOTE 2 — For information on the current status of USB documents, see the USB Implementors Forum at <http://www.usb.org>.

*Serial ATA 2.6 (SATA-26)*. 15 February 2007

NOTE 3 — For information on the current status of Serial ATA documents, see the Serial ATA International Organization at <http://www.sata-io.org>.

PANTONE® Color Formula Guide

NOTE 4 — Pantone® and PANTONE MATCHING SYSTEM® are registered trademarks of Pantone, Inc. For more information on Pantone colors, contact Pantone, Inc. at <http://www.pantone.com>.

### 3 Definitions, symbols, abbreviations, and conventions

#### 3.1 Definitions

**3.1.1 aggregation:** When used in class diagrams, a form of association that defines a whole-part relationship between the whole (i.e., aggregate) and its parts.

**3.1.2 association:** When used in class diagrams a relationship between two or more classes that specifies connections among their objects (i.e., relationship that specifies that objects of one class are connected to objects of another class).

**3.1.3 Information Unit (IU):** An IU is a formatted collection of data which carries command, task management function, response, read ready, or write ready information. See 6.2.

#### 3.2 Symbols and abbreviations

Abbreviation	Meaning
XOR	exclusive logical OR
^	exclusive logical OR
x	multiplication
/	division
≠ or NE	not equal
≤ or LE	less than or equal to
±	plus or minus
≈	approximately
x	multiply
+	add
-	subtract
< or LT	less than
= or EQ	equal
> or GT	greater than
≥ or GE	greater than or equal to
AWG	American wire gauge
DUT	Device under test
EMI	Electromagnetic interference
EMC	Electromagnetic compatibility
ESD	Electrostatic discharge
ISI	Intersymbol interference
IU	Information Unit
LSB	Least significant bit

LUN	Logical unit number
MSB	Most significant bit
SBC-2	SCSI Block Commands-2 (see 2.3)
SPC-3	SCSI Primary Commands-3 (see 2.3)

### 3.3 Keywords

**3.3.1 invalid:** A keyword used to describe an illegal or unsupported bit, byte, word, field or code value. Receipt by a device server of an invalid bit, byte, word, field or code value shall be reported as error.

**3.3.2 mandatory:** A keyword indicating an item that is required to be implemented as defined in this standard.

**3.3.3 may:** A keyword that indicates flexibility of choice with no implied preference.

**3.3.4 may not:** A keyword that indicates flexibility of choice with no implied preference.

**3.3.5 obsolete:** A keyword indicating that an item was defined in prior SCSI standards but has been removed from this standard.

**3.3.6 option, optional:** Keywords that describe features that are not required to be implemented by this standard. However, if any optional feature defined by this standard is implemented, then it shall be implemented as defined in this standard.

**3.3.7 reserved:** A keyword referring to bits, bytes, words, fields, and code values that are set aside for future standardization. A reserved bit, byte, word, or field shall be set to zero, or in accordance with a future extension to this standard. Recipients are not required to check reserved bits, bytes, words, or fields for zero values. Receipt of reserved code values in defined fields shall be reported as error.

**3.3.8 shall:** A keyword indicating a mandatory requirement. Designers are required to implement all such mandatory requirements to ensure interoperability with other products that conform to this standard.

**3.3.9 should:** A keyword indicating flexibility of choice with a strongly preferred alternative.

**3.3.10 vendor specific:** Something (e.g., a bit, field, code value) that is not defined by this standard. Specification of the referenced item is determined by the SCSI device vendor and may be used differently in various implementations.

### 3.4 Editorial conventions

Certain words and terms used in this standard have a specific meaning beyond the normal English meaning. These words and terms are defined either in the glossary or in the text where they first appear.

Upper case is used when referring to the name of a numeric value defined in this specification or a formal attribute possessed by an entity. When necessary for clarity, names of objects, procedure calls, arguments or discrete states are capitalized or set in bold type. Names of fields are identified using small capital letters (e.g., NACA bit).

Names of procedure calls are identified by a name in bold type (e.g., **Execute Command**). Names of arguments are denoted by capitalizing each word in the name (e.g., Sense Data is the name of an argument in the **Execute Command** procedure call).

Quantities having a defined numeric value are identified by large capital letters (e.g., CHECK CONDITION). Quantities having a discrete but unspecified value are identified using small capital letters. (e.g., TASK COMPLETE,

indicates a quantity returned by the **Execute Command** procedure call). Such quantities are associated with an event or indication whose observable behavior or value is specific to a given implementation standard.

Lists sequenced by letters (e.g., a-red, b-blue, c-green) show no priority relationship between the listed items. Numbered lists (e.g., 1-red, 2-blue, 3-green) show a priority ordering between the listed items.

If a conflict arises between text, tables, or figures, the order of precedence to resolve the conflicts is text; then tables; and finally figures. Not all tables or figures are fully described in the text. Tables show data format and values.

Notes and examples do not constitute any requirements for implementors.

## 3.5 Numeric and character conventions

### 3.5.1 Numeric conventions

A binary number is represented in this standard by any sequence of digits comprised of only the Arabic numerals 0 and 1 immediately followed by a lower-case b (e.g., 0101b). Underscores or spaces may be included in binary number representations to increase readability or delineate field boundaries (e.g., 0 0101 1010b or 0\_0101\_1010b).

A hexadecimal number is represented in this standard by any sequence of digits comprised of only the Arabic numerals 0 through 9 and/or the upper-case English letters A through F immediately followed by a lower-case h (e.g., FA23h). Underscores or spaces may be included in hexadecimal number representations to increase readability or delineate field boundaries (e.g., B FD8C FA23h or B\_FD8C\_FA23h).

A decimal number is represented in this standard by any sequence of digits comprised of only the Arabic numerals 0 through 9 not immediately followed by a lower-case b or lower-case h (e.g., 25).

This standard uses the following conventions for representing decimal numbers:

- a) the decimal separator (i.e., separating the integer and fractional portions of the number) is a period;
- b) the thousands separator (i.e., separating groups of three digits in a portion of the number) is a space; and
- c) the thousands separator is used in both the integer portion and the fraction portion of a number.

Table 2 shows some examples of decimal numbers using various numbering conventions.

**Table 2 — Numbering conventions**

French	English	This standard (new column)
0,6	0.6	0.6
3,141 592 65	3.14159265	3.141 592 65
1 000	1,000	1 000
1 323 462,95	1,323,462.95	1 323 462.95

A decimal number represented in this standard with an overline over one or more digits following the decimal point is a number where the overlined digits are infinitely repeating (e.g., 666.6 means 666.666 666... or 666 2/3, and 12.142 857 means 12.142 857 142 857... or 12 1/7).

### 3.5.2 Byte encoded character strings conventions

When this standard requires one or more bytes to contain specific encoded characters, the specific characters are enclosed in single quotation marks. The single quotation marks identify the start and end of the characters that are required to be encoded but are not themselves to be encoded. The characters that are to be encoded are shown in the case that is to be encoded.

An ASCII space character (i.e., 20h) may be represented in a string by the character '␣' (e.g., 'SCSI␣device').

The encoded characters and the single quotation marks that enclose them are preceded by text that specifies the character encoding methodology and the number of characters required to be encoded.

EXAMPLE - Using the notation described in this subclause, stating that eleven ASCII characters 'SCSI device' are to be encoded would be the same writing out the following sequence of byte values: 53h 43h 53h 49h 20h 64h 65h 76h 69h 63h 65h.

## 4 Model

### 4.1 Overview

This standard works with USB Full Speed devices and higher. A USB target shall support a single I\_T nexus.

---

---

Editor's Note 2: This subclause describes the 4 pipe USB model where 2 pipes are command and status, and 2 pipes are data in/out

---

---

### 4.2 Placeholder

## 5 USB

### 5.1 Overview

This clause describes all information associated with USB to support this transport. This includes USB descriptors and backward compatibility with existing mass storage protocols.

### 5.2 Backward Compatibility

This transport shall coexist with other USB Mass storage protocols and interfaces

### 5.3 USB Resource Requirements

#### 5.3.1 Overview

This transport requires one Device Descriptor, one Configuration Descriptor, one Interface Descriptor, and two Endpoint Descriptors (Bulk-in and Bulk-Out). This transport also utilizes the control endpoint.

#### 5.3.2 USB Class Specific Requests

---



---

Editor's Note 3: Should we add something here to return the maximum queue depth?

---



---

#### 5.3.3 USB Descriptors

##### 5.3.3.1 Device Descriptor

**Table 3 — USB Device Descriptor**

Bit Byte	7	6	5	4	3	2	1	0
0	B LENGTH (12h)							
1	B DESCRIPTOR TYPE (01h)							
2	(LSB)							
3	(MSB)	BCD USB						
4	B DEVICE CLASS (00h)							
5	B DEVICE SUBCLASS (00h)							
6	B DEVICE PROTOCOL (00h)							
7	B MAX PACKET SIZE							
8	(LSB)							
9	(MSB)	ID VENDOR						
10	(LSB)							
11	(MSB)	ID PRODUCT						
12	(LSB)							
13	(MSB)	BCD DEVICE						
14	I MANUFACTURER							
15	I PRODUCT							
16	I SERIAL NUMBER							
17	B NUM CONFIGURATIONS							

See USB-20 for a description of all the fields in this descriptor.

---

Editor's Note 4: Do we want to specify WWN somewhere here, possibly in place of or as the serial number?

---

### 5.3.3.2 Configuration Descriptor

**Table 4 — USB Configuration Descriptor**

Bit Byte	7	6	5	4	3	2	1	0
0	B LENGTH (09h)							
1	B DESCRIPTOR TYPE (02h)							
2	(LSB)							
3								
4	B NUM INTERFACES							
5	B CONFIGURATION VALUE							
6	I CONFIGURATION							
7	Reserved	SELF POWERD	REMOTE WAKEUP	Reserved				
8	MAX POWER							

See USB-20 for the description of all the fields in this descriptor.

### 5.3.3.3 Interface Descriptor

**Table 5 — USB Interface Descriptor**

Bit Byte	7	6	5	4	3	2	1	0
0	B LENGTH (09h)							
1	B DESCRIPTOR TYPE (04h)							
2	B INTERFACE NUMBER							
3	B ALTERNATE SETTING							
4	B NUM ENDPOINTS							
5	B INTERFACE CLASS							
6	B INTERFACE SUBCLASS							
7	B INTERFACE PROTOCOL							
8	I INTERFACE							

See USB-20 for the description of all the fields in this descriptor.

The B INTERFACE PROTOCOL field shall be set to xx (will be assigned by USB).



### 5.3.3.4 Endpoint Descriptors

**Table 6 — USB Bulk-In Endpoint Descriptor**

Bit Byte	7	6	5	4	3	2	1	0
0	B LENGTH (07h)							
1	B DESCRIPTOR TYPE (05h)							
2	DIR (1b)	Reserved			ENDPOINT NUMBER			
3	BM ATTRIBUTES (02h)							
4	W MAX PACKET SIZE (LSB)							
5								
6	Reserved							

See USB-20 for the description of all the fields in this descriptor.

The W MAX PACKET SIZE field shall be greater than or equal to 16.

**Table 7 — USB Bulk-Out Endpoint Descriptor**

Bit Byte	7	6	5	4	3	2	1	0
0	B LENGTH (07h)							
1	B DESCRIPTOR TYPE (05h)							
2	DIR (0b)	Reserved			ENDPOINT NUMBER			
3	BM ATTRIBUTES (02h)							
4	(LSB)							
5	(MSB)	W MAX PACKET SIZE						
6	Reserved							

See USB-20 for the description of all the fields in this descriptor.

The W MAX PACKET SIZE field shall be greater than or equal to 16.

## 5.4 Backward Compatibility

---



---

Editor's Note 5: USB devices may present support for this standard as an alternate interface. This would allow an existing host to detect a legacy interface. Newer hosts would look for alternate interfaces and turn on UAS.

---



---

## 6 Transport

### 6.1 Overview

This clause describes the transport protocol. This includes Information Units, data transfer sequences, and transport management.

### 6.2 Information Units

#### 6.2.1 Overview

Table 8 is a summary of the information units described in this subclause.

**Table 8 — IU Identifier Summary**

Identifier	Description	Reference
00h	Reserved	
01h	COMMAND IU	6.2.2
02h	Reserved	
03h	SENSE IU	6.2.5.1
04h	RESPONSE IU	6.2.5.2
05h	TASK MANAGEMENT IU	6.2.6
06h	READ READY IU	6.2.3
07h	WRITE READY IU	6.2.4
08h..FFh	Reserved	

#### 6.2.2 Command IU

Each Command IU shall be sent in a single USB packet. The Command IU shall not share a packet with any other Information Unit or data. Table 9 describes the Command IU.

**Table 9 — Command IU**

Byte	Bit	7	6	5	4	3	2	1	0
0		COMMAND IU ID (01h)							
1		Reserved							
2	(MSB)	INITIATOR PORT TRANSFER TAG							
3		(LSB)							
4	(MSB)	LENGTH							
5		(LSB)							
6	Reserved	TASK PRIORITY				TASK ATTRIBUTE			
7		Reserved							
8		LOGICAL UNIT NUMBER							
15									
16		CDB							
31									
32		ADDITIONAL CDB BYTES							
33..LENGTH+5									

The COMMAND IU ID of 01h defines the format of the IU that follows.

The LENGTH field defines the number of bytes in this Command IU following the LENGTH field. The LENGTH field shall be greater than 15. This is the number of bytes needed to transport a six byte CDB.

The INITIATOR PORT TRANSFER TAG field is defined in SAM-4.

The LOGICAL UNIT NUMBER field contains the address of the logical unit. The structure of the LOGICAL UNIT NUMBER field shall be as defined in SAM-4. If the addressed logical unit does not exist, the task manager shall follow the rules for selection of incorrect logical units defined in SAM-4.

The TASK PRIORITY field specifies the relative scheduling of the task containing this command in relation to other tasks already in the task set, if the tasks have SIMPLE task attributes (see SAM-4).

The TASK ATTRIBUTE field is defined in table 10.

**Table 10 — TASK ATTRIBUTE field**

Code	Task Attribute	Description
000b	SIMPLE	Specifies that the task be managed according to the rules for a simple task attribute (see SAM-4).
001b	HEAD OF QUEUE	Specifies that the task be managed according to the rules for a head of queue task attribute (see SAM-4).
010b	ORDERED	Specifies that the task be managed according to the rules for an ordered task attribute (see SAM-4).
011b	Reserved	
100b	ACA	Specifies that the task be managed according to the rules for an automatic contingent allegiance task attribute (see SAM-4).
101b..111b	Reserved	

### 6.2.3 Read Ready IU

The Read Ready IU is sent by a target port to inform the initiator port that the target is ready to send data for a read command or a bidirectional command. Table 16 describes the Read Ready IU.

**Table 11 — Read Ready IU**

Bit Byte	7	6	5	4	3	2	1	0
0	READ READY IU ID (06h)							
1	Reserved							
2	(MSB)							
3	INITIATOR PORT TRANSFER TAG (LSB)							

The READ READY IU ID of 06h defines the format of the IU that follows.

The INITIATOR PORT TRANSFER TAG field is defined in SAM-4.

### 6.2.4 Write Ready IU

The Write Ready IU is sent by a target port to request write data from the initiator port during a write command or a bidirectional command. Table 16 describes the Write Ready IU.

**Table 12 — Write Ready IU**

Bit Byte	7	6	5	4	3	2	1	0
0	TRANSFER READY IU ID (07h)							
1	Reserved							
2	(MSB)							
3	INITIATOR PORT TRANSFER TAG (LSB)							

The WRITE READY IU ID of 07h defines the format of the IU that follows.

The INITIATOR PORT TRANSFER TAG field is defined in SAM-4.

## 6.2.5 Status IUs

### 6.2.5.1 Sense IU

The Sense IU is used to pass status from the target to the initiator. Each Sense IU shall be sent in a single USB packet. The Sense IU shall not share a packet with any other Information Unit or data. Table 13 describes the Sense IU.

**Table 13 — Sense IU**

Bit Byte	7	6	5	4	3	2	1	0
0	SENSE IU ID (03h)							
1	Reserved							
2	(MSB) INITIATOR PORT TRANSFER TAG (LSB)							
3								
4	LENGTH							
5								
6	STATUS							
7	Reserved							
8	SENSE DATA							
LENGTH + 5								

The SENSE IU ID of 03h defines the format of the IU that follows.

The INITIATOR PORT TRANSFER TAG field is defined in SAM-4.

The LENGTH field defines the number of bytes in this Status Unit following the LENGTH field. The LENGTH field shall be greater than 0002h.

The STATUS field shall be set to the status code for the command that has ended (see SAM-4 for a list of status codes).

The SENSE DATA field shall be set to the sense data (see SAM-4). If no SENSE DATA is available, then the LENGTH field shall be set to 0002h.

### 6.2.5.2 Response IU

The Response IU is used to pass task management status information from the target to the initiator. Each Response IU shall be sent in a single USB packet. The Response IU shall not share a packet with any other Information Unit or data. Table 14 describes the Response IU.

**Table 14 — Response IU**

Bit Byte	7	6	5	4	3	2	1	0
0	RESPONSE IU ID (04h)							
1	Reserved							
2	(MSB) INITIATOR PORT TRANSFER TAG (LSB)							
3								
4	ADDITIONAL RESPONSE INFORMATION							
6								
7	RESPONSE CODE							

The RESPONSE IU ID of 04h defines the format of the IU that follows.

The INITIATOR PORT TRANSFER TAG field is defined in SAM-4.

The ADDITIONAL RESPONSE INFORMATION field contains additional response information for certain task management functions (e.g., QUERY UNIT ATTENTION) as defined in SAM-4. ADDITIONAL RESPONSE

INFORMATION shall be set to 00000000h if the task management function does not define ADDITIONAL RESPONSE INFORMATION or the logical unit does not support response information.

Table 15 defines the RESPONSE CODE field, which specifies the error condition or the completion status of a task management function. See 6.2.6 for the mapping of these response codes to SCSI service responses.

**Table 15 — RESPONSE CODE field**

Code	Description
00h	TASK MANAGEMENT FUNCTION COMPLETE <sup>a</sup>
01h	Reserved
02h	INVALID INFORMATION UNIT
03h	Reserved
04h	TASK MANAGEMENT FUNCTION NOT SUPPORTED <sup>a</sup>
05h	TASK MANAGEMENT FUNCTION FAILED <sup>a</sup>
06h	Reserved
07h	Reserved
08h	TASK MANAGEMENT FUNCTION SUCCEEDED <sup>a</sup>
09h	INCORRECT LOGICAL UNIT NUMBER <sup>a</sup>
0Ah	OVERLAPPED TAG ATTEMPTED <sup>b</sup>
0Bh-FFh	Reserved
<sup>a</sup> Only valid when responding to a Task Unit. <sup>b</sup> Returned in case of command/task management function or task management function/task management function tag conflicts.	

### 6.2.6 Task Management IU

The Task Management IU is sent by an initiator to request that a task management function be processed by the task manager in a logical unit. Table 16 describes the Task Management IU.

**Table 16 — Task Management IU**

Bit Byte	7	6	5	4	3	2	1	0
0	TASK MANAGEMENT IU ID (05h)							
1	Reserved							
2	(MSB)	INITIATOR PORT TRANSFER TAG						(LSB)
3								
4	TASK MANAGEMENT FUNCTION							
5	Reserved							
6	(MSB)	TAG OF TASK TO BE MANAGED						(LSB)
7								
8								
15	LOGICAL UNIT NUMBER							

The TASK MANAGEMENT IU ID of 05h defines the format of the IU that follows.

The INITIATOR PORT TRANSFER TAG field is defined in SAM-4.

Table 17 defines the TASK MANAGEMENT FUNCTION field.

**Table 17 — Task Management Functions**

Code	Task management function	Uses the LOGICAL UNIT NUMBER field	Uses the TAG OF TASK TO BE MANAGED field	Description
00h	Reserved			
01	ABORT TASK	yes	yes	The task manager shall perform the ABORT TASK task management function with L set to the value of the LOGICAL UNIT NUMBER field and Q set to the value of the TAG OF TASK TO BE MANAGED field (see SAM-4). <sup>a</sup>
02h	ABORT TASK SET	yes	no	The task manager shall perform the ABORT TASK SET task management function with L set to the value of the LOGICAL UNIT NUMBER field (see SAM-4). <sup>a</sup>
03h	Reserved			
04h	CLEAR TASK SET	yes	no	The task manager shall perform the CLEAR TASK SET task management function with L set to the value of the LOGICAL UNIT NUMBER field (see SAM-4). <sup>a</sup>
05h-07h	Reserved			
08h	LOGICAL UNIT RESET	yes	no	The task manager shall perform the LOGICAL UNIT RESET task management function with L set to the value of the LOGICAL UNIT NUMBER field (see SAM-4). <sup>a</sup>
09h-0Fh	Reserved			
10h	I_T NEXUS RESET	no	no	The task manager shall perform the I_T NEXUS RESET task management function (see SAM-4). <sup>a</sup>
11h-3Fh	Reserved			
40h	CLEAR ACA	yes	no	The task manager shall perform the CLEAR ACA task management function with L set to the value of the LOGICAL UNIT NUMBER field (see SAM-4). <sup>a</sup>
41h-7Fh	Reserved			
80h	QUERY TASK	yes	yes	The task manager shall perform the QUERY TASK task management function with L set to the value of the LOGICAL UNIT NUMBER field and Q set to the value of the TAG OF TASK TO BE MANAGED field (see SAM-4). <sup>a</sup>
81h	QUERY TASK SET	yes	no	The task manager shall perform the QUERY TASK SET task management function with L set to the value of the LOGICAL UNIT NUMBER field (see SAM-4). <sup>a</sup>
82h	QUERY UNIT ATTENTION	yes	no	The task manager shall perform the QUERY UNIT ATTENTION task management function with L set to the value of the LOGICAL UNIT NUMBER field (see SAM-4). <sup>a</sup>
83h-FFh	Reserved			
<sup>a</sup> The task manager shall perform the specified task management function with the I and T arguments set to the initiator port and target port involved in the connection used to deliver the Task Management IU.				

If the TASK MANAGEMENT FUNCTION field contains a reserved or unsupported value, the task manager shall return a Response IU with the RESPONSE CODE field set to TASK MANAGEMENT FUNCTION NOT SUPPORTED.

If the TASK MANAGEMENT FUNCTION field is set to ABORT TASK or QUERY TASK, the TAG OF TASK TO BE MANAGED field specifies the TAG value from the Command IU that contained the task to be aborted or checked. For all other task management functions, the TAG OF TASK TO BE MANAGED field shall be ignored.

The LOGICAL UNIT NUMBER field contains the address of the logical unit. The structure of the LOGICAL UNIT NUMBER field shall be as defined in SAM-4. If the addressed logical unit does not exist, the task manager shall return a Response IU with the RESPONSE CODE field set to INCORRECT LOGICAL UNIT NUMBER.

## 6.3 Information Unit Sequences

### 6.3.1 Send Data-In

### 6.3.2 Receive Data-Out

Need to add ping-pong diagrams that show sequence of events.

## 6.4 Transport Requirements

### 6.4.1 Data Transfer Transport Portocol Services

Once the device has started processing the Data-In delivery service or the Data-Out delivery service for the I\_T\_L\_Q the device shall complete the Data-In or Data-out service before beginning another Data-In or Data-Out service for the I\_T nexus.

## 6.5 Asynchronous Notification

---

---

Editor's Note 6: Since SAM-4 does not define a mechanism for Asynchronous Status Notificiatoin, we may need to define one here. This would remove the need to poll in removable media devices.

---

---

## 6.6 Virtualization

Place holder.





**Annex A**  
(Normative)

**Place Holder**

**A.1 Overview**